

# SPINCAT

DOWNHOLE TOOLS BY **STONEAGE**



## FIVE MODELS FOR DOWNHOLE CLEANING

The SpinCat family features five models, each one specific to different coil tubing sizes. Our newest model is the SC-125 (See the chart below.) All SpinCat models are self-rotating, and easy to maintain in the field.

## FEATURES & BENEFITS

- Rotating Assembly for Complete Coverage
- Simple Maintenance – Field Serviceable
- Durable Fluoro – Elastomer Seals
- Computerized Flow Calculations
- Controlled Rotation – Increases Cleaning Power
- Carbide Nozzles – Deliver the Hardest Hitting, Longest Lasting Jet Possible

## SPINCAT™ Specifications

Model	SC-125	SC-168	SC-212	SC-250	SC-287
Max Pressure	5,000 psi (345 bar)	5,000 psi (345 bar)	5,000 psi (345 bar)	5,000 psi (345 bar)	5,000 psi (345 bar)
Flow Range	0.5-1.5 bpm (80-240 l/min)	0.7-1.3 bpm (111-207 l/min)	0.8-2.0 bpm (127-318 l/min)	1.0-3.0 bpm (160-480 l/min)	1.0-3.0 bpm (160-480 l/min)
Flow Rating	2.3 Cv	2.3 Cv	4.6 Cv	7.5 Cv	7.5 Cv
Outside Diameter	1.25 in. (32 mm)	1.68 in. (43 mm)	2.12 in. (54 mm)	2.50 in. (64 mm)	2.87 in. (73 mm)
Overall Length	8.3 in. (203 mm)	9.8 in. (250 mm)	12.3 in. (312 mm)	16 in. (406 mm)	15.6 in. (396 mm)
Inlet	7/8" AMMT Inlet	1" AMMT	1-1/2" AMMT	1-1/2" AMMT	2-3/8" PAC
Rotation Speed	10-50 rpm	150-200 rpm	150-200 rpm	80-150 rpm	80-150 rpm
Weight	1.9 lb (0.86 kg)	4.6 lb (2 kg)	8.9 lb (4 kg)	15.9 lb (7.2 kg)	20 lb (9.1 kg)
PSI Loss @ 1 bpm	330 psi (23 bar)	330 psi (23 bar)	83 psi (6 bar)	31 psi (2 bar)	31 psi (2 bar)
Maximum Temp	390° F (200° C)	390° F (200° C)	390° F (200° C)	390° F (200° C)	390° F (200° C)
Safe Working Load	8,500 lb Tension 12,000 lb Compression	8,500 lb Tension 12,000 lb Compression	15,000 lb Tension 21,000 lb Compression	20,000 lb Tension 25,000 lb Compression	20,000 lb Tension 25,000 lb Compression

